

CONTENTS

	Page
CONTENTS.....	vi
LIST OF TABLES.....	viii
LIST OF FIGURES.....	ix
LIST OF ABBREVIATIONS AND SYMBOLS.....	x
CHAPTER	
1 INTRODUCTION.....	1
1.1 Overview.....	1
1.2 Principle for selecting materials.....	2
1.3 Review of Literatures.....	11
1.4 Objective.....	15
1.5 Benefits.....	15
2 EXPERIMENTAL TECHNIQUES.....	16
2.1 Chemicals and Instruments.....	16
2.1.1 Chemicals.....	16
2.1.2 Instruments.....	18
2.2 Procedures.....	20
2.2.1 Solvent selections.....	20
2.2.2 The determination of solvent evaporation.....	25
2.2.3 The Measurement of viscosity.....	26
2.2.4 Film Coating on plastic.....	27
2.2.5 The measurement of adhesion of film on plastic.....	28

CONTENTS (Continued)

	Page
3 RESULTS AND DISCUSSION.....	30
3.1 The viscosity and paint adhesion.....	30
3.1.1 Viscosity and the characteristic of adhesion when the solvent mixtures of toluene, 2-propanol and ethyl acetate is used.....	30
3.1.2 Viscosity and the characteristic of the paint on plastic when the solvent mixtures of toluene, xylene, o-xylene, p-xylene, m-xylene, ethanol, 1-butanol, 1-propanol, n-butyl acetate, ethyl acetate and propyl acetate is used.....	33
3.2 The evaporation of solvents.....	40
3.2.1 Effect of time to the amount evaporating of the mixture.....	40
3.2.2 The effect of stirring to the amount evaporating.....	41
3.2.3 The effect of temperature to the amount evaporating.....	42
3.2.4 The determination of the evaporation rate of solvent mixtures.....	43
4 CONCLUSION.....	48
BIBLIOGRAPHY.....	51
APPENDIX.....	55
A.....	56
B.....	109
C.....	117
D.....	125
E.....	129
VITAE.....	130

LIST OF TABLES

Table	Page
1.1 Solubility parameters of the solvents.....	6
2.1 Solvents used with sources and prices.....	17
2.2 Paint samples for plastic printing under investigations.....	18
2.3 Various ratios of solvent mixtures of toluene, 2-propanol and ethyl acetate.....	21
2.4 Various kinds of solvent with the ratio 6:3:1 by volume.....	23
3.1 Viscosity and the characteristic of adhesion of the currently-used solvent mixtures with various ratios at room temperature.....	30
3.2 Viscosity and the characteristic of the paint on plastic for various solvents with the ratio of 6:3:1 by volume at room temperature.....	33
3.3 The ratio of the solvent mixtures with the viscosity and adhesion appropriate to be the thinners.....	36
3.4 Various kinds of solvent, ratios 6:3:1 by volume, with the viscosity and adhesion appropriate to be the thinners.....	37
3.5 The evaporation rate (mg/min) of each currently-used solvent with various ratio of mixing.....	44
3.6 The evaporation rate (mg/min) of various solvents with the ratio of 6:3:1 by volume.....	45

LIST OF FIGURES

Figure	Page
1.1 Scheme of interaction sphere of the studied resin.....	12
2.1 A film applicator.....	19
2.2 Viscosity cup No. 4.....	20
2.3 Viscosity measurement by using viscosity cup No. 4.....	27
2.4 Coating the paint onto plastic by film applicator.....	27
2.5 Classification of adhesion test results.....	29
3.1 The example of the test results for the adhesion study in the case of solvent mixtures.....	39
3.2 The graph showing the relationship between time and peak areas as the amount evaporating of toluene, xylene, ethyl acetate, n-butyl acetate, 1-propanol and 2-propanol at the temperature of 25 ± 3 °C.....	40
3.3 The graph to show the relationship between stirring rate and peaks areas which is the amount evaporating of 2-propanol, ethyl acetate, 1-propanol, n-butyl acetate, toluene and xylene respectively at the stirring rates of 0, 600, 900 and 1200 rpm at the temperature of 25 ± 3 °C for 25 min.....	41
3.4 The graph showing the relationship between the temperature and peak areas as the amount evaporating of toluene, xylene, ethyl acetate, n-butyl acetate, 1-propanol and 2-propanol at the temperature of 40, 50 and 60 °C for a period of 25 min.....	42

LIST OF ABBREVIATIONS AND SYMBOLS

δ	=	Solubility parameter
δ_d	=	Dispersion solubility parameter
δ_h	=	Hydrogen bonding solubility parameter
δ_m	=	Moderately hydrogen bonded solubility parameter
δ_n	=	Nonpolar solubility parameter
δ_p	=	Polar solubility parameter
δ_p	=	Poorly hydrogen bonded solubility parameter
δ_s	=	Strongly hydrogen bonded solubility parameter
$^{\circ}\text{C}$	=	degree Celsius
cm^3/min	=	cubic centimeter per minute
l	=	liter
mg/min	=	milligram per minute
min	=	minute
ml	=	milliliter
mm	=	millimeter
μl	=	micro liter
μm	=	micrometer
rpm	=	revolution per minute