

## TABLE OF CONTENTS

Executive Summary	i
Publications Derived from Results of the Project	iv
Acknowledgements	v
List of Tables	ix
List of Figures	x
<b>CHAPTER ONE</b>	
<b>INTRODUCTION</b>	1
1.1 Overview of the Project	1
1.2 Overview of Natural Rubber	1
1.3 Natural Rubber in Thailand	3
1.3.1 Planting area	3
1.3.2 Rubber production	3
1.4 Trend of Rubber Industry in Thailand	7
1.5 Planning of Project	7
1.5.1 Surveying of rubber smoking factories to acquire basic data	8
1.5.2 Energy auditing of rubber smoking process	8
1.5.3 Study on factors affecting rubber drying	8
1.5.4 Theoretical work and field trial of air drier to accelerate rubber smoking process	8
<b>CHAPTER TWO</b>	
<b>SURVEYING OF RUBBER SMOKING FACTORIES</b>	9
2.1 Introduction	9
2.2 Planning of Survey	9
2.3 Rubber Smoking Technique	10
2.3.1 Making of rubber sheets	10
2.3.2 Making of smoked sheets	13
2.3.3 Source of energy	13
2.3.4 Smoking rooms and furnaces	14

2.4 Energy Used in the Process	18
2.5 Discussion	24
2.6 Conclusion	25
<b>CHAPTER THREE</b>	
<b>MONITORING OF RUBBER SMOKING PROCESS</b>	26
3.1 Introduction	26
3.2 Materials and Methods	26
3.3 Energy Aspect of Smoking Process	27
3.4 Moisture Aspect of Smoking Process	33
3.5 General Discussion	41
3.6 Conclusion	43
<b>CHAPTER FOUR</b>	
<b>FACTORS AFFECTING RUBBER DRYING PROCESS</b>	45
4.1 Introduction	45
4.2 Factors Affecting Rubber Sheet Drying Process	46
4.2.1 Materials and methods	46
4.2.2 Results and discussion	50
4.2.3 General discussion	55
4.3 Trial Test with Green and Dry Firewood	57
4.3.1 The experiment	57
4.3.2 Results and discussion	58
4.4 Conclusion	61
<b>CHAPTER FIVE</b>	
<b>DEVELOPMENT OF HEAT PUMP AIR DRIER (HPAD)</b>	64
5.1 Introduction	64
5.2 Principle of HPAD	65
5.3 Laboratory-scale HPAD	69
5.3.1 Construction	69
5.3.2 Theoretical background of refrigeration cycle	69
5.3.3 Experimentation with simple air drier	75

5.3.4	Enhancing dehumidification by bypass technique	75
5.3.5	Experimentation with bypass technique	77
5.4	Design and Construction of Full-Scale HPAD	80
5.4.1	Determination of cooling capacity	80
5.4.2	Modification of conventional air conditioner	81
5.5	HPAD-Assisted Rubber Smoking	82
5.5.1	Installation and experimentation procedure	82
5.5.2	Results and discussion	82
5.6	Conclusion	92
<b>CHAPTER SIX</b>		
<b>CONCLUSION AND RECOMMENDATION</b>		93
6.1	Conclusion	93
6.2	Recommendation	94
APPENDIX A	EQUATIONS FOR ENERGY ANALYSIS	95
APPENDIX B	ECONOMIC ANALYSIS OF INSTALLATION OF INSULATION	99
APPENDIX C	PHOTO COLLECTION OF PROJECT ACTIVITIES	101
APPENDIX D	REFERENCES	106

## LIST OF TABLES

Table 1.1	Rubber planting area by province	4
Table 1.2	Projection of Thailand's rubber production during 1992-1996	6
Table 1.3	Current and forecasted of world rubber production	6
Table 2.1	Number of factories visited by provinces	11
Table 2.2	Survey data of double layer rooms	19
Table 2.3	Survey data of single layer rooms	20
Table 2.4	Analysed data	21
Table 3.1	Basic data of experiments	29
Table 3.2	Energy analysis for the smoking process	30
Table 3.3	Water in the process	38
Table 4.1	Programme of experiments	49
Table 4.2	Results of experiments	51
Table 4.3	Firewood used : green and dry conditions	59
Table 5.1	Results of experiment on 1-ton air drier	76
Table 5.2	Results of trial test of HPAD	84
Table 5.3	Results of HPAD-assisted smoking	86
Table 5.4	Analysed result of HPAD-assisted smoking	87
Table 5.5	Effects of HPAD on rubber smoking	91

## LIST OF FIGURES

Figure 1.1	Rubber planting area in Thailand	5
Figure 2.1	Geographical locations of factories visited	12
Figure 2.2	Double layer room	15
Figure 2.3	Single layer room (outside furnace)	16
Figure 2.4	Single layer room (furnace beneath)	17
Figure 2.5	Effect of loading density on specific wood consumption of double layer rooms	22
Figure 3.1	Description of the smoking room and parameters to be measured	28
Figure 3.2	Typical smoking room temperature	31
Figure 3.3	Typical heat loss rate through walls	32
Figure 3.4	Typical accumulative heat loss through walls	34
Figure 3.5	Typical exhaust loss calculated with reference to surroundings	35
Figure 3.6	Typical accumulative heat loss via the exhaust	36
Figure 3.7	Typical exhaust and inlet humidity ratios	39
Figure 3.8	Typical accumulative mass of water emitted by firewood, extracted from rubber and admitted with inlet air	40
Figure 3.9	Flow of water in the rubber smoking process	42
Figure 4.1	Environmentally controlled chamber	47
Figure 4.2	Effects of inlet air relative humidity on drying time	52
Figure 4.3	Effects of air flow rate on drying time (40% RH)	54
Figure 4.4	Result of actual loading density ( $63.73 \text{ kg/m}^3$ )	56
Figure 4.5	Firewood consumption of room #3 (green wood) and #4 (dry wood)	60
Figure 4.6	Accumulative firewood consumption	62
Figure 4.7	Humidity ratio of gas exhausted from rooms #3 and #4	63
Figure 5.1	Rotary sorption wheel air drier	66
Figure 5.2	Principle of refrigeration cycle modified for air drier	67
Figure 5.3	Close cycle heat pump air drier	68
Figure 5.4	Laboratory-scale HPAD	70

Figure 5.5	Covering hood for laboratory-scale HPAD and parameters measured	71
Figure 5.6	Vapor compression refrigeration cycle	72
Figure 5.7	First law analysis of mixture cooled by an evaporator	74
Figure 5.8	First law analysis of mixture heated by a condenser	74
Figure 5.9	Enhancing air dehumidification by bypass technique	78
Figure 5.10	Air dehumidification with recuperators	79
Figure 5.11	Air drier constructed for field trial	83
Figure 5.12	Connection of HPAD to furnace	85
Figure 5.13	Humidity ratios of inlet and exhaust	88-89