

บทคัดย่อ

งานวิจัยนี้เป็นการหาประสิทธิภาพของวัสดุ 4 ชนิดคือ คินลูกรัง หินปูนฝุ่น ปูนขาวและ ถ้ำลอยในการดูดซับสารหนูที่ปนเปื้อนในดินจาก อ.ร่อนพิบูลย์ จ.นครศรีธรรมราช เพื่อหาชนิดของวัสดุ กลุ่มดินที่มีประสิทธิภาพสูงในการดูดซับและตรึงสารหนูที่สะสมอยู่ในดินไม่ให้เคลื่อนที่ขึ้นสู่ผิวดิน และ ฟุ้งกระจายออกสู่อากาศ ประกอบด้วยการศึกษาทดลองแบบกะและแบบต่อเนื่อง โดยผลการทดลองแบบกะพบว่า เมื่อใช้อัตราส่วนการผสมระหว่างวัสดุกลุ่มดินและดินที่ปนเปื้อนสารหนูที่ 10% w/w ประสิทธิภาพในการ ดูดซับสารหนูเรียงจากมากไปหาน้อยดังนี้ ถ้ำลอย คินลูกรัง ปูนขาว และหินปูนฝุ่น มีประสิทธิภาพในการ ดูดซับสารหนुर้อยละ 84, 60, 38, และ 1 ตามลำดับและจากการศึกษาเวลาที่เข้าสู่สภาวะสมดุล รวมถึง ไอโซเทอมของคินลูกรัง และถ้ำลอยที่พีเอช 4 7 และ 12 พบว่าที่พีเอช 4 คินลูกรังจะเข้าสู่สภาวะสมดุล ภายใน 4 ชม. ส่วนที่พีเอช 7 และ 12 จะใช้เวลา 6 ชม. สำหรับถ้ำลอยที่พีเอช 12 จะเริ่มเข้าสู่สภาวะสมดุล ภายใน 2 ชม. ส่วนที่พีเอช 4 และ 7 จะใช้เวลา 6 ชม. นอกจากนี้คินลูกรังยังมีสมดุลของการดูดซับสูงสุดที่ พีเอช 7 และ 4 และลักษณะไอโซเทอมของการดูดซับเป็นแบบ Langmuir ส่วนถ้ำลอยมีสมดุลของการดูดซับ สูงสุดที่พีเอช 12 และ 7 และลักษณะไอโซเทอมของการดูดซับที่พีเอช 12 เป็นแบบ Freundlich และพีเอช 7 เป็นแบบ Langmuir สำหรับการทดลองแบบต่อเนื่องเพื่อศึกษาการเคลื่อนที่ของสารหนูที่ละลายอยู่ในน้ำ ผ่านชั้นดินและประสิทธิภาพการดูดซับสารหนูของคินลูกรังและถ้ำลอย พบว่าการชะละลายด้วยน้ำกลั่น ปราศจากไอออน (deionized water) ถ้ำลอยสามารถดูดซับสารหนูได้ดีกว่าคินลูกรังและเพิ่มพีเอชของ สารละลาย และการชะละลายด้วย K_2SO_4 0.05 โมล คินลูกรังจะสามารถดูดซับสารหนูได้ดีกว่าถ้ำลอยและ ลดพีเอชของสารละลาย

ผลการวิจัยบ่งชี้ได้ว่าคินลูกรังมีความเหมาะสมในการนำไปใช้ดูดซับและตรึงสารหนูได้ ดีในสภาวะที่มีพีเอชต่ำ ส่วนถ้ำลอยมีความเหมาะสมในการนำไปใช้ดูดซับและตรึงสารหนูได้ดีในสภาวะ ที่มีพีเอชสูง นอกจากนี้ไอโซเทอมของ Langmuir และ Freundlich สามารถนำไปใช้ในการคำนวณปริมาณวัสดุ กลุ่มดินที่จะใช้ในการป้องกันการฟุ้งกระจายของดินที่ปนเปื้อนสารหนูสู่อากาศได้

ABSTRACT

The determination of the arsenic adsorption efficiency of 4 types of soil covering materials i.e. lateritic soil, limestone powder, lime, and fly ash on arsenic contaminated soil obtained from Romphiboon District, Nakhon Sri Thammarat Province was investigated to identify the types of soil covering materials with high arsenic adsorption efficiency for solving an arsenic air pollution problem. The investigation included a batch adsorption test and a column leaching test. The result of the batch adsorption test revealed that the proportion between soil covering materials and arsenic contaminated soil at 10 % w/w, the efficiency of arsenic adsorption of fly ash, lateritic soil, lime and limestone powder were 84, 60, 38 and 1 % respectively. The equilibrium time for lateritic soil at pH 4 was achieved within 4 hrs, whereas pH 7 and 12, the equilibrium time was 6 hrs. For fly ash, 2 hrs were required to reach the equilibrium at pH 12, while the equilibrium time was attained within 6 hrs at pH 4 and 7. Furthermore, lateritic soil possessed the high arsenic adsorption efficiency at pH 7 and 4 and best fit with the Langmuir isotherm. The fly ash showing the high arsenic adsorption efficiency at pH 12 and 7 fit the Freundlich isotherm at $\text{pH} \bar{1}2$ and Langmuir isotherm at pH 7. Column leaching test to investigate the arsenic mobility through soil layer and arsenic adsorption efficiency of lateritic soil and fly ash were also carried out. The result showed that fly ash with deionized water leachate possessed higher arsenic adsorption efficiency than that of lateritic soil and increasing the pH of the leachate with time, whereas lateritic soil with K_2SO_4 0.05 M leachate had higher arsenic adsorption efficiency than that of fly ash and lowering the pH of the leachate with time.

The results of this study revealed that lateritic soil was suitable for arsenic adsorption in the low pH environment, whilst fly ash was appropriate for arsenic adsorption in the high pH environment. Furthermore, Langmuir and Freundlich isotherms could be employed to determine the amounts of soil covering materials to prevent arsenic air pollution.