

## บรรณานุกรม

กัมพล ทองเรือง. 2547. การวิเคราะห์วงจรไฟฟ้า. สถาบันบูรณา, หน้า 435-446. ปทุมธานี.

ชิตชัย สุทธาสวิน. 2524. 108 วงศ์ปรีโภน. ศรีสุทธา, หน้า 5-54. กรุงเทพฯ.

ธนกร คีรพิทักษ์, ประชุมนันท์ นิลสุข, นวัชชัย อินทุไส และ สุนี อินทุไส. 2541. ทฤษฎีเครื่องเสียง,  
สถาบันบูรณา, ปทุมธานี.

วรพงศ์ ตั้งศรีรัตน์. 2548. เชนเซอร์และทรานส์ดิวเซอร์. กรุงเทพฯ: สมาคมส่งเสริมเทคโนโลยี  
(ไทย-ญี่ปุ่น).

สมศักดิ์ กีรติวุฒิศรีย์. 2549. หลักการและการใช้งานเครื่องมือวัดอุตสาหกรรม. หน้า 25(1)-  
25(12). กรุงเทพฯ: สมาคมส่งเสริมเทคโนโลยี (ไทย-ญี่ปุ่น).

สาขันต์ ชื่นอารමณ์. 2549. ช่างสร้างเครื่องเสียงทรานซิสเตอร์และไอซี. หน้า 133-224. กรุงเทพฯ:  
สมาคมส่งเสริมเทคโนโลยี (ไทย-ญี่ปุ่น).

อดิศักดิ์ จิตภูษา. 2548. ไฟอิโซเชรามิกที่มีและไม่มีตะกั่วสำหรับการใช้งานเป็นไฮโดรโฟน.  
วิทยานิพนธ์วิทยาศาสตรมหาบัณฑิต มหาวิทยาลัยสงขลานครินทร์.

Bao-Jin Chu, Da-Ren Chen, Guo-Rong Li and Qing-Rui Yin. 2002. Electrical Properties of  
 $\text{Na}_{1/2}\text{Bi}_{1/2}\text{TiO}_3\text{-BaTiO}_3$  ceramics. pp. 2115-2121.

Birol, H. Damjanovic, D. Setter, N. 2005. Preparation and characterization of  $(\text{Na}_{0.5}\text{K}_{0.5})\text{NbO}_3$   
ceramics.

Bowen, C.R., Perry, A. Lewis A.C.F. and Kara H. 2004. Processing and properties of  
porous piezoelectric materials with high hydrostatic figures of merit. J. of the  
European Ceramic Society. Vol.24, pp. 541-545.

C. Alie, R. Pirard, J.P. Pirard. 200. Mercury porosimetry applied to porous silica materials successive buckling and intrusion mechanisms. Coll. Surf. A :187–188.

Daoli Zhang, Dongxiang, Shenglin Jiang, Xiaohong and Shuping Dgong 2003. Effect of porosity on the electrical characteristics of current-limiting BaTiO<sub>3</sub>-based positive- temperature-coefficient (PCT) ceramic thermistors coated with electroless nickel-phosphorous electrode. Sensor and Actuator.

D.F.K. Hennings, Dielectric materials for sintering in reducing atmospheres,J. Euro. Ceram. Soc. 21 (2001) 1637–1642.Y.-K. Kim et al. / Journal of Materials Processing Technology 152 (2004) 276–283 283

D. Li et al., 2006, Cymbal piezoelectric composite underwater acoustic transducer, Journal of ultrasonics, 127.

F.A.L. Dullien, Porous Media: Fluid Transport and Pore Structure,second ed., Academic Press, New York, 1992.

F. R. Abbott et al., United State Patent, Patent No. 2,895,062,1959

G. de With, Structural integrity of ceramic multilayer capacitor materials and ceramic multilayer capacitors, J. Euro. Ceram. Soc. 12 (1993) 323–336.

G.P. Matthews, C.J. Ridgway, M.C. Spssearing, Void space modeling of mercury intrusion hysteresis in sandstone, J. Coll. Interface Sci.171 (1995) 8–27.

G.Yiping, K. Ken-ichi and O. Hitoshi, 2004, Structure and Electrical Properties of lead-free (Na<sub>0.5</sub>K<sub>0.5</sub>)NbO<sub>3</sub>-BaTiO<sub>3</sub> ceramics : Jpn.J.Appl.Phys., Vol. 43, 9B, pp. 6662-6666.

H. Chazono, Y. Inomata, N. Kohzu, H. Kishi, in: N. Mizutani, K. Shinozaki, N. Kambara, T. Kimura (Eds.), *Electroceramics in Japan II*, Trans. Trech. Publications Ltd., CSJ Series, vol. 5, 1999.

H. Chazono, Y. Okino, N. Kohzu, H. Kishi, Effect of Sm and Ho addition on the microstructure and electrical properties in MLCC with Ni internal electrode, *Ceram. Trans.* 97 (1999) 53–64.

Hewlett Packard Application Note 339-13. 1987. Measuring the dielectric constant of solid materials.

H. Jaffe et al., United State Patent, Patent No. 2,592,703, 1952

IEEE Standard on Piezoelectricity. 1987. ANSI/IEEE standards 176-1987, The institute of Electrical and Electronics Engineers, Inc, New York.

Jordan T.L., Prasad S.E. and Wallace J.B. 1996. Piezoelectric ceramics characterization, ICASE Report No. 2001-28.

J. W. Crownover et al., United State Patent, Patent No. 2,836,738, 1958.

Kara, H., Ramesh, R., Stevens, R. and Bowen, C.R. 2003. Porous PZT ceramics for receiving transducers., *IEEE Transactions on Ultrasonics*. Vol.50 p. 289-296.

K. Hirakata, S. Sato, F. Uchikoba, Y. Kosaka, K. Sawamura, Multilayer capacitors with copper inner electrodes, *Ferroelectrics* 133 (1992) 139–144.

L. Moscou, S. Lub, Practical use of mercury porosimetry in the study of porous solids, *Power Tech.* 29 (1981) 45–52.

Mason W.P., Fellow., IRE. And Jaffe H. 1954. Methods for measuring piezoelectric, elastic, and dielectric coefficients of crystals and ceramic., Proc. of the IRE. p. 921-932.

Millar C.E., Andersen B., Ringgard E., Wolny W., Ricote J., and Pardo L. 1995. Fabrication of high density, fine-grained PZT ceramics using a post-sinter HIP treatment., Proceedings of the Ninth IEEE International Symposium.p.118-121.

M.J. Cima, M. Dudziak, J.A. Lewis, Observation of poly(vinylbutyral)-dibutyl phthalate binder capillary migration, J. Am. Ceram.Soc. 24 (1989) 1087–1090.

N. Das, H.S. Maiti, Formation of pore structure in tape-cast alumina membranes—effects of binder content and firing temperature, J. Membr. Sci. 140 (1998) 205–212.

N. Halder, D. Chattopadhyay, A.D. Sharma, D. Saha, A. Sen, H.S.Maiti, Effect of sintering atmosphere on the dielectric properties of barium titanate based capacitors, Mater. Res. Bull. 36 (1991) 905–913.

Ramesh R., Kara H. and Bowen C.R. 2002. The dielectric mechanical and piezoelectric properties of 3-3 piezoelectric composites., Ferroelectrics., Vol. 273 p. 383-388.

Rashid, M. H., Microelectronic Circuits analysis and design, PWS, 1999, 442-448.

R. E. Newnham et al ., United State Patent, Patent No. 5,729,077, 1998

R. J. Penneck et al., United State Patent, Patent No. 4,794,295, 1988

Roncari E., Galassi C., Craciun F., Capiani C. and Piancastelli A. 2000. A microstructural study of porous piezoelectric ceramics obtained by different methods., Journal of the European Ceramic Society. Vol. 21 p. 409-417.

- Setter N. 2002. Pizoelectric materials in devices. Switzerland : EPFL Swiss Federal Institute of Technology.
- S. Lowell, J.E. Shields, Powder Surface Area and Porosity, third ed., Chapman Hall, New York, 1991.
- S. Masia, P. Calvert, W.E. Rhine, H.K. Bowen, Effect of oxides on binder burnout during ceramics processing, *J. Mater. Sci.* 24 (1989) 1907–1912.
- S. Westermarck, A.M. Juppo, L. Kervinen, J. Yliruusi, Pore structure and surface area of mannitol powder, granules and tablets determined with mercury porosimetry and nitrogen adsorption, *Euro. J. Pharm. Biopharm.* 46 (1998) 61–68.
- T. Nomura, T. Kato, Y. Nagano, Proceedings of the Ninth US–Japan Seminar on Dielectric and Piezoelectric Ceramics, 1999, pp. 295–298.
- T. Tsurumi, Y. Yamanoto, N. Ohashi, H. Chazono, Y. Inomata, H. Kishi, Proceedings of the 9th US–Japan Seminar on Dielectric and Piezoelectric Ceramics, 1999, p. 345.
- Uchino K. 2000. Ferroelectric devices, New York : Marcel Dekker, Inc.
- V. M. Ristie, 1983, Principles of Acoustic Devices John Wiley and Sons, Inc.
- Y. Mizuno, T. Hagiwara, H. Chazono, H. Kishi, Effect of milling process on core-shell microstructure and electrical properties for BaTiO<sub>3</sub>-based Ni-MLCC, *J. Euro. Ceram. Soc.* 21 (2001) 1649–1652.
- Y. Mizuno, Y. Okino, N. Kohzu, H. Chazono, H. Kishi, Influence of the microstructure evolution on electrical properties of multilayer capacitors with Ni electrode, *Jpn. J. Appl. Phys.* 37 (1998) 5227–5231.

Y. Okino, N. Kohzu, Y. Mizuno, M. Honda, H. Chazono, H. Kishi, Effects of the microstructure on dielectric properties for BaTiO<sub>3</sub>-based MLC with Ni electrode, Key Eng. Mater. 157 (1999) 9–15.

Young-Kil Kim<sup>a</sup>, Yeon-Gil Jung <sup>a</sup>, Tae-Hyun Sung<sup>b</sup>, Dae-Hawn Kim<sup>c</sup>, Ungyu Paik <sup>c</sup>,  
a Department of Ceramic Science and Engineering, Changwon National University,  
Changwon, Kyungnam 641-773, South Korea

Y. Park, Y.H. Kim, H.G. Kim, The effect of grain size on dielectric behavior of BaTiO<sub>3</sub>-based X7R materials, Mater. Lett. 28 (1996) 101–106.

Y. Sakabe, Dielectric materials for base-metal multilayer ceramic capacitors, Am. Ceram. Soc. Bull. 66 (1987) 1338–1341.